



NOTES:

1. MATERIAL: WHITE POLYESTER + MYLAR COATING(半霧面), $t=0.15\pm0.05\text{mm}$.
ADHESIVE: # K.K. NO. 9 OR EQUIVALENT.
2. BACKGROUND'S COLOR: BLACK. WORD'S COLOR: WHITE
3. "-" LABEL VENDER IN ENGLISH NAME, 2 LETTERS.
4. LABEL MUST BE DIE CUT PROPERLY AS PER DIMENSION.
5. LABEL MUST BE UL RECOGNIZED: PGDQ2 OR PGJ12 AND CSA CERTIFIED: Plastic Group III(polycarbonate).
6. THE LABEL IS SUPPOSED TO BE PASTED ON PC CASE EVENLY AND PROPERLY IT'S NOT ALLOWED TO HAVE ANY BULGE HAPPEN ON THE LABEL AFTER BE BURNT IN 72 HRS IN OVEN WHICH TEMPERATURE IS 100°C .
7. DIMENSIONS MARKED * MARK MUST BE INSPECTED AND CONTROLLED STRICTLY BY IQC.
8. THE PLASTIC MATERIAL OF APPLICATION SURFACE FOR THIS LABEL IS PC.
9. ALL SPECIFICATION MUST BEEN APPROVED BY DESIGN ENGINEER.
10. UNFOUNDED TOLERANCE: $\pm 0.2\text{mm}$.
11. THE FINISHED LABEL GOODS SHOULD ALL THE SAME AS THIS DRAWING; INCLUDING: FONT TYPE, SYMBOLS, CONTENT, SIZE, POSITION,ETC.
12. 黏貼於PC塑膠材質 表面屬於光面或是鏡面

SCALE:
UNIT: mm

P/N.: 6LL21111XXGP

MODEL NO.:	FSP120-AHAN3	TITLE:	SPEC LABEL	SHEET: 1 OF 1	REV: 02
R&D3 Division	PE	ME	DATE		
L.J	Melody	Melody	2024/02/15		
INTERIOR COUNTERSIGN:					

MD6510